



LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:119.73V I:0.1167A P:13.783W PF:0.9863 Freq:59.98Hz		
UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1006.77x1 lm		
NAME: AD-3-S15W-FC-5CCT-WH	TYPE:	WEIGHT:
SPEC.: 5000K	DIM.:	SERIAL No.:
MFR.: Light by Lotus	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA			
MODEL	AD-3-S15W-FC-5CCT-WH	Imax (cd)	7511	S/MH (C0/180)	0.31
NOMINAL POWER (W)	15	LOR (%)	100.0	S/MH (C90/270)	0.40
RATED VOLTAGE (V)	120	TOTAL FLUX (lm)	1006.8	η UP, DN (C0-180)	0.0, 36.7
NOMINAL FLUX (lm)	1006.77	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.0, 63.3
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	0.00
TEST VOLTAGE (V)	120	η down (%)	100.0	CIBSE SHR MAX	0.30



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 24.3 °C
 Operators:
 Test Date: 2024-09-25

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
 Humidity: 65.0%
 Test Distance: 3.087m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	2339	1829	1742	2083	2814	3925	4175	3302	0- 10	408.0	408.0	40.5,40.5
20	614.8	432.1	392.4	539.0	769.2	1048	1113	878.5	10- 20	406.8	814.8	80.9,80.9
30	39.84	36.59	36.06	37.95	39.38	57.95	78.32	44.36	20- 30	126.7	941.5	93.5,93.5
40	22.55	19.89	19.38	21.00	24.50	28.26	29.31	26.72	30- 40	20.39	961.9	95.5,95.5
50	15.64	15.01	14.96	15.37	15.79	16.30	16.38	16.13	40- 50	14.36	976.3	97,97
60	12.11	11.75	11.79	12.06	12.49	13.06	13.10	12.69	50- 60	12.59	988.9	98.2,98.2
70	7.498	6.850	6.880	7.486	8.493	9.575	9.608	8.545	60- 70	10.41	999.3	99.3,99.3
80	2.830	2.279	2.350	2.849	3.554	4.296	4.325	3.646	70- 80	5.847	1005	99.8,99.8
90	0.2362	0.1189	0.1099	0.1582	0.3328	0.5111	0.5516	0.2823	80- 90	1.653	1007	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:24.3 °C
 Operators:
 Test Date:2024-09-25

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
 Humidity:65.0%
 Test Distance:3.087m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:119.73V I:0.1167A P:13.783W PF:0.9863 Freq:59.98Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1006.77x1 lm		
NAME: AD-3-S15W-FC-5CCT-WH	TYPE:	WEIGHT:
SPEC.: 5000K	DIM.:	SERIAL No.:
MFR.: Light by Lotus	SUR.:	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	3015	1792
80	4237	3518
75	5008	4443
70	5699	5230
65	6386	6045
60	6296	6128
55	6321	6000
50	6325	6049
45	6375	6042


C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 24.3 °C
 Operators:
 Test Date: 2024-09-25

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
 Humidity: 65.0%
 Test Distance: 3.087m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:119.73V I:0.1167A P:13.783W PF:0.9863 Freq:59.98Hz		
UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1006.77x1 lm		
NAME: AD-3-S15W-FC-5CCT-WH	TYPE:	WEIGHT:
SPEC.: 5000K	DIM.:	SERIAL No.:
MFR.: Light by Lotus	SUR.:	Shielding Angle:

ρcc	80%			70%			50%			30%			10%			0
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															
	Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.13	1.11	1.09	1.11	1.09	1.07	1.07	1.05	1.04	1.03	1.02	1.01	.99	.99	.98	.96
2.0	1.07	1.04	1.02	1.06	1.03	1.00	1.02	1.00	.98	.00	.98	.96	.97	.96	.94	.93
3.0	1.03	.99	.96	1.01	.98	.95	.99	.96	.94	.97	.94	.92	.94	.93	.91	.90
4.0	.99	.95	.92	.98	.94	.91	.96	.93	.90	.94	.91	.89	.92	.90	.88	.87
5.0	.95	.91	.88	.94	.91	.88	.93	.89	.87	.91	.88	.86	.90	.87	.85	.84
6.0	.92	.88	.85	.91	.88	.85	.90	.87	.84	.89	.86	.84	.88	.85	.83	.82
7.0	.89	.85	.82	.89	.85	.82	.88	.84	.82	.87	.84	.81	.86	.83	.81	.80
8.0	.87	.83	.80	.86	.82	.80	.85	.82	.79	.85	.81	.79	.84	.81	.79	.78
9.0	.84	.80	.78	.84	.80	.78	.83	.80	.77	.83	.79	.77	.82	.79	.77	.76
10.0	.82	.78	.76	.82	.78	.76	.81	.78	.76	.81	.78	.75	.80	.77	.75	.74



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:24.3 °C
 Operators:
 Test Date:2024-09-25

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
 Humidity:65.0%
 Test Distance:3.087m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:119.73V I:0.1167A P:13.783W PF:0.9863 Freq:59.98Hz		
UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1006.77x1 lm		
NAME: AD-3-S15W-FC-5CCT-WH	TYPE:	WEIGHT:
SPEC.: 5000K	DIM.:	SERIAL No.:
MFR.: Light by Lotus	SUR.:	Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.142	.081	.026	.135	.077	.024	.123	.070	.022	.111	.064	.021	.101	.058	.019	
2.0	.131	.072	.022	.125	.069	.021	.115	.064	.020	.105	.059	.019	.097	.055	.017	
3.0	.121	.064	.019	.116	.062	.019	.108	.058	.018	.100	.055	.017	.093	.051	.016	
4.0	.112	.058	.017	.109	.057	.017	.101	.054	.016	.095	.051	.015	.088	.048	.015	
5.0	.105	.054	.016	.102	.052	.015	.096	.050	.015	.090	.048	.014	.085	.045	.014	
6.0	.099	.050	.014	.096	.049	.014	.091	.047	.014	.086	.045	.013	.081	.043	.013	
7.0	.093	.046	.013	.091	.045	.013	.086	.044	.013	.082	.042	.012	.078	.041	.012	
8.0	.089	.043	.012	.086	.043	.012	.082	.041	.012	.079	.040	.011	.075	.039	.011	
9.0	.084	.041	.011	.082	.040	.011	.079	.039	.011	.076	.038	.011	.072	.037	.011	
10.0	.080	.039	.011	.079	.038	.011	.076	.037	.010	.073	.036	.010	.070	.035	.010	

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.169	.158	.148	.144	.135	.127	.099	.093	.088	.057	.054	.051	.018	.017	.017	
2.0	.151	.133	.118	.129	.114	.102	.088	.079	.071	.051	.046	.042	.016	.015	.014	
3.0	.136	.113	.095	.116	.098	.083	.080	.068	.058	.046	.040	.034	.015	.013	.011	
4.0	.123	.098	.079	.106	.085	.068	.073	.059	.048	.042	.035	.028	.014	.011	.009	
5.0	.112	.086	.066	.097	.074	.057	.067	.052	.040	.039	.030	.024	.012	.010	.008	
6.0	.103	.076	.056	.089	.065	.048	.061	.046	.034	.036	.027	.020	.011	.009	.007	
7.0	.096	.067	.048	.082	.058	.041	.057	.041	.029	.033	.024	.017	.011	.008	.006	
8.0	.089	.061	.041	.077	.053	.036	.053	.037	.025	.031	.022	.015	.010	.007	.005	
9.0	.083	.055	.036	.072	.048	.031	.050	.033	.022	.029	.020	.013	.009	.006	.004	
10.0	.078	.050	.031	.067	.043	.027	.047	.031	.019	.027	.018	.012	.009	.006	.004	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:24.3°C
 Operators:
 Test Date:2024-09-25

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
 Humidity:65.0%
 Test Distance:3.087m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:119.73V I:0.1167A P:13.783W PF:0.9863 Freq:59.98Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1006.77x1 lm		
NAME: AD-3-S15W-FC-5CCT-WH	TYPE:	WEIGHT:
SPEC.: 5000K	DIM.:	SERIAL No.:
MFR.: Light by Lotus	SUR.:	Shielding Angle:

ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2

Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	10.6	11.3	10.8	11.4	11.6	10.4	11.1	10.6	11.2	11.4
3H	12.2	12.9	12.5	13.0	13.2	11.9	12.6	12.2	12.7	12.9
4H	12.8	13.4	13.1	13.6	13.8	12.4	13.0	12.7	13.2	13.4
6H	13.2	13.7	13.4	13.9	14.2	12.7	13.3	13.0	13.5	13.7
8H	13.3	13.8	13.5	14.0	14.3	12.8	13.3	13.1	13.6	13.8
12H	13.3	13.8	13.6	14.1	14.3	12.8	13.3	13.1	13.6	13.8
4H 2H	11.3	11.9	11.6	12.1	12.3	11.2	11.7	11.4	11.9	12.2
3H	13.0	13.5	13.3	13.8	14.1	12.8	13.3	13.1	13.5	13.8
4H	13.7	14.1	14.0	14.4	14.7	13.3	13.8	13.7	14.1	14.4
6H	14.1	14.5	14.5	14.8	15.2	13.7	14.1	14.1	14.4	14.8
8H	14.2	14.6	14.6	14.9	15.3	13.8	14.2	14.1	14.5	14.9
12H	14.3	14.6	14.7	15.0	15.4	13.8	14.1	14.2	14.5	14.9
8H 4H	13.8	14.2	14.2	14.5	14.9	13.5	13.9	13.9	14.3	14.6
6H	14.3	14.6	14.7	15.0	15.4	13.9	14.3	14.4	14.7	15.1
8H	14.5	14.8	14.9	15.2	15.6	14.1	14.3	14.5	14.8	15.2
12H	14.6	14.8	15.0	15.2	15.7	14.1	14.3	14.5	14.8	15.2
12H 4H	13.8	14.1	14.2	14.5	14.9	13.5	13.9	13.9	14.2	14.6
6H	14.3	14.6	14.8	15.0	15.5	13.9	14.2	14.4	14.7	15.1
8H	14.5	14.7	14.9	15.2	15.6	14.1	14.3	14.5	14.8	15.2

Variations with the observer position at spacings(CIE Pub.117):		
S = 1.0H	+ 0.2 / - 0.3	+ 0.2 / - 0.3
1.5H	+ 0.1 / - 0.2	+ 0.1 / - 0.2
2.0H	+ 0.2 / - 0.4	+ 0.2 / - 0.4

CIE Pub.117, 1007 lm Total Lamp Luminous Flux Corrected (8log(F/F0) = 0.0)
Area: 0.0038465 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:24.3°C
Operators:
Test Date:2024-09-25

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
Humidity:65.0%
Test Distance:3.087m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:119.73V I:0.1167A P:13.783W PF:0.9863 Freq:59.98Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1006.77x1 lm		
NAME: AD-3-S15W-FC-5CCT-WH	TYPE:	WEIGHT:
SPEC.: 5000K	DIM.:	SERIAL No.:
MFR.: Light by Lotus	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	89	83	79	88	83	79	88	82	79	76
0.80	96	90	87	95	90	87	94	89	86	83
1.00	100	95	91	99	94	91	98	94	90	86
1.25	104	99	95	103	98	95	101	97	94	90
1.50	106	102	98	105	101	98	103	99	97	93
2.00	109	105	102	107	104	101	105	102	99	94
2.50	110	107	104	109	105	103	106	103	101	95
3.00	112	109	106	110	107	105	107	105	103	96
4.00	114	111	109	112	110	108	108	106	105	98
5.00	115	113	111	113	111	110	109	108	107	99
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended				SHRNOM = 1.25			

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 24.3 °C
 Operators:
 Test Date: 2024-09-25

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
 Humidity: 65.0%
 Test Distance: 3.087m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:119.73V I:0.1167A P:13.783W PF:0.9863 Freq:59.98Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1006.77x1 lm		
NAME: AD-3-S15W-FC-5CCT-WH	TYPE:	WEIGHT:
SPEC.: 5000K	DIM.:	SERIAL No.:
MFR.: Light by Lotus	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 24.3°C
 Operators:
 Test Date: 2024-09-25

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
 Humidity: 65.0%
 Test Distance: 3.087m [K=1.0000]
 Remarks:

AAI CURVES

Test:U:119.73V I:0.1167A P:13.783W PF:0.9863 Freq:59.98Hz		
UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1006.77x1 lm		
NAME: AD-3-S15W-FC-5CCT-WH	TYPE:	WEIGHT:
SPEC.: 5000K	DIM.:	SERIAL No.:
MFR.: Light by Lotus	SUR.:	Shielding Angle:




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 24.3 °C
 Operators:
 Test Date: 2024-09-25

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
 Humidity: 65.0%
 Test Distance: 3.087m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

Test:U:119.73V I:0.1167A P:13.783W PF:0.9863 Freq:59.98Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1006.77x1 lm		
NAME: AD-3-S15W-FC-5CCT-WH	TYPE:	WEIGHT:
SPEC.: 5000K	DIM.:	SERIAL No.:
MFR.: Light by Lotus	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 24.3 °C
 Operators:
 Test Date: 2024-09-25

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
 Humidity: 65.0%
 Test Distance: 3.087m [K=1.0000]
 Remarks:

LED Avg.L Report

Test:U:119.73V I:0.1167A P:13.783W PF:0.9863 Freq:59.98Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:1006.77x1 lm		
NAME: AD-3-S15W-FC-5CCT-WH	TYPE:	WEIGHT:
SPEC.: 5000K	DIM.:	SERIAL No.:
MFR.: Light by Lotus	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	6581
L_0~180 (75) av	5413
L_0~180 (85) av	3988
L_90~270 (65) av	6533
L_90~270 (75) av	5568
L_90~270 (85) av	4285
L_45 (65) av	6586
L_45 (75) av	5502
L_45 (85) av	4170

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:24.3℃
 Operators:
 Test Date:2024-09-25

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
 Humidity:65.0%
 Test Distance:3.087m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 24.3 °C
 Operators:
 Test Date: 2024-09-25

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.00.460
 Humidity: 65.0%
 Test Distance: 3.087m [K=1.0000]
 Remarks:

