



LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:119.95V I:0.1300A P:11.294W PF:0.9497 Freq:59.98Hz Lamp Flux:1015.23x1 lm		
NAME: LED-6-S12W-5CCTWH-SQ	TYPE:	WEIGHT:
SPEC.:4000K 80	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 89.89 lm/W			
MODEL		I _{max} (cd)	367.6	S/MH (C0/180)	1.24
NOMINAL POWER (W)	12	LOR (%)	100.0	S/MH (C90/270)	1.24
RATED VOLTAGE (V)	120	TOTAL FLUX (lm)	1015.2	<input type="checkbox"/> UP, DN (C0-180)	0.0, 50.3
NOMINAL FLUX (lm)	1015.23	CIE CLASS	DIRECT	<input type="checkbox"/> UP, DN (C180-360)	0.0, 49.7
LAMPS INSIDE	1	<input type="checkbox"/> up (%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE (V)	120	<input type="checkbox"/> down (%)	100.0	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators:
 Test Date: 2021-12-30

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity: 65.0%
 Test Distance: 3.080m [K=1.0000]
 Remarks: PORTER

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


mm	C0	C45	C90	C135	C180	C225	C270	C315	mm	□ zone	□ total	%lum, lamp
10	360.2	360.1	359.9	359.1	358.8	359.5	359.1	359.6	0- 10	34.66	34.66	3.41,3.41
20	340.2	340.7	339.4	338.3	337.8	338.3	337.9	339.2	10- 20	98.96	133.6	13.2,13.2
30	307.5	308.4	306.6	305.2	304.4	305.1	305.0	306.7	20- 30	149.2	282.8	27.9,27.9
40	264.8	266.2	263.9	262.3	261.0	262.2	261.6	263.9	30- 40	178.7	461.5	45.5,45.5
50	214.0	215.2	212.8	211.4	209.9	211.2	211.0	213.5	40- 50	184.0	645.5	63.6,63.6
60	156.7	158.3	155.7	153.8	152.1	153.5	153.1	155.9	50- 60	164.6	810.1	79.8,79.8
70	96.01	97.67	94.70	92.97	91.27	92.56	91.58	94.43	60- 70	123.1	933.2	91.9,91.9
80	39.15	39.32	36.23	35.12	35.31	35.12	33.79	36.23	70- 80	67.82	1001	98.6,98.6
90	0.1806	0.1747	0.1686	0.1776	0.3085	0.3086	0.2964	0.2940	80- 90	14.25	1015	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-12-30

□ Range: 0 - 90DEG
 □ Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:3.080m [K=1.0000]
 Remarks: PORTER

LUMINANCE LIMITATION CURVES

Test:U:119.95V I:0.1300A P:11.294W PF:0.9497 Freq:59.98Hz Lamp Flux:1015.23x1 lm		
NAME: LED-6-S12W-5CCTWH-SQ	TYPE:	WEIGHT:
SPEC.:4000K 80	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	1576	1019
80	2029	1878
75	2316	2247
70	2526	2492
65	2693	2671
60	2821	2802
55	2920	2902
50	2995	2979
45	3061	3045


C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-12-30

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:3.080m [K=1.0000]
 Remarks: PORTER

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:119.95V I:0.1300A P:11.294W PF:0.9497 Freq:59.98Hz Lamp Flux:1015.23x1 lm		
NAME: LED-6-S12W-5CCTWH-SQ	TYPE:	WEIGHT:
SPEC.:4000K 80	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:

□cc	80%			70%			50%			30%			10%			0
□w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
□fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.04	1.00	.96	1.02	.98	.95	.98	.95	.92	.94	.91	.89	.90	.88	.86	.84
2.0	.91	.84	.78	.89	.83	.78	.85	.80	.76	.82	.78	.74	.79	.76	.72	.70
3.0	.80	.72	.65	.78	.71	.65	.75	.69	.64	.73	.67	.62	.70	.65	.61	.59
4.0	.71	.62	.55	.69	.61	.55	.67	.60	.54	.65	.58	.53	.62	.57	.53	.51
5.0	.63	.54	.48	.62	.54	.47	.60	.53	.47	.58	.51	.46	.56	.50	.46	.44
6.0	.57	.48	.42	.56	.48	.41	.54	.47	.41	.52	.46	.41	.51	.45	.40	.38
7.0	.52	.43	.37	.51	.42	.37	.49	.42	.36	.48	.41	.36	.46	.40	.36	.34
8.0	.47	.39	.33	.46	.38	.33	.45	.38	.32	.44	.37	.32	.43	.37	.32	.30
9.0	.43	.35	.29	.43	.35	.29	.41	.34	.29	.40	.34	.29	.39	.33	.29	.27
10.0	.40	.32	.27	.39	.32	.27	.38	.31	.27	.37	.31	.26	.37	.31	.26	.25



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-12-30

□ Range: 0 - 90DEG
 □ Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:3.080m [K=1.0000]
 Remarks: PORTER

WEC AND CCEC

Test:U:119.95V I:0.1300A P:11.294W PF:0.9497 Freq:59.98Hz Lamp Flux:1015.23x1 lm		
NAME: LED-6-S12W-5CCTWH-SQ	TYPE:	WEIGHT:
SPEC.:4000K 80	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio		Wall Exitance Coefficients (WEC)			
0.0						
1.0	.302 .172 .054	.295 .168 .054	.282 .162 .052	.270 .156 .050	.259 .150 .048	
2.0	.287 .157 .048	.281 .155 .048	.269 .150 .046	.258 .145 .045	.248 .141 .044	
3.0	.267 .142 .043	.261 .140 .042	.251 .136 .041	.241 .132 .041	.232 .129 .040	
4.0	.247 .128 .038	.242 .127 .037	.233 .123 .037	.224 .120 .036	.216 .118 .036	
5.0	.228 .116 .034	.224 .115 .034	.216 .112 .033	.208 .110 .033	.201 .108 .032	
6.0	.212 .106 .030	.208 .105 .030	.201 .103 .030	.194 .101 .030	.188 .099 .029	
7.0	.198 .098 .028	.194 .097 .028	.188 .095 .027	.182 .093 .027	.176 .091 .027	
8.0	.185 .090 .025	.182 .089 .025	.176 .088 .025	.170 .086 .025	.165 .085 .025	
9.0	.173 .084 .023	.170 .083 .023	.165 .082 .023	.160 .080 .023	.156 .079 .023	
10.0	.163 .078 .022	.160 .077 .022	.156 .076 .021	.151 .075 .021	.147 .074 .021	

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio		Ceiling Cavity Exitance Coefficients (CCEC)			
0.0	.190 .190 .190	.163 .163 .163	.111 .111 .111	.064 .064 .064	.020 .020 .020	
1.0	.180 .156 .135	.154 .134 .116	.105 .092 .080	.061 .053 .047	.019 .017 .015	
2.0	.172 .132 .099	.147 .114 .085	.101 .079 .059	.058 .046 .035	.019 .015 .011	
3.0	.164 .114 .075	.140 .099 .065	.096 .068 .045	.056 .040 .027	.018 .013 .009	
4.0	.156 .101 .059	.134 .087 .051	.092 .061 .036	.053 .036 .021	.017 .012 .007	
5.0	.149 .091 .047	.128 .078 .041	.088 .055 .029	.051 .032 .017	.016 .010 .006	
6.0	.142 .082 .039	.122 .071 .034	.084 .050 .024	.049 .029 .014	.016 .010 .005	
7.0	.135 .075 .033	.116 .065 .029	.080 .046 .021	.047 .027 .012	.015 .009 .004	
8.0	.129 .069 .029	.111 .060 .025	.077 .042 .018	.045 .025 .011	.014 .008 .004	
9.0	.122 .064 .025	.106 .056 .022	.073 .039 .016	.043 .023 .009	.014 .008 .003	
10.0	.117 .060 .023	.101 .052 .020	.070 .037 .014	.041 .022 .008	.013 .007 .003	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-12-30

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:3.080m [K=1.0000]
 Remarks: PORTER

UGR(Unified Glare Rating) Table

Test:U:119.95V I:0.1300A P:11.294W PF:0.9497 Freq:59.98Hz Lamp Flux:1015.23x1 lm										
NAME: LED-6-S12W-5CCTWH-SQ					TYPE:			WEIGHT:		
SPEC.:4000K 80					DIM.:			SERIAL No.:		
MFR.:					SUR.:			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	16.6	18.1	16.9	18.3	18.5	16.6	18.1	16.9	18.3	18.5
3H	18.1	19.5	18.4	19.7	20.0	18.1	19.5	18.4	19.7	19.9
4H	18.7	20.0	19.0	20.2	20.5	18.6	19.9	18.9	20.2	20.5
6H	19.1	20.3	19.4	20.6	20.9	19.0	20.2	19.3	20.5	20.8
8H	19.1	20.3	19.5	20.6	20.9	19.1	20.3	19.4	20.5	20.8
12H	19.2	20.3	19.5	20.6	20.9	19.1	20.2	19.4	20.5	20.8
4H 2H	17.2	18.5	17.5	18.8	19.1	17.2	18.5	17.5	18.8	19.0
3H	18.9	20.0	19.2	20.3	20.6	18.9	20.0	19.2	20.3	20.6
4H	19.6	20.6	20.0	21.0	21.3	19.5	20.6	19.9	20.9	21.3
6H	20.1	21.0	20.5	21.4	21.7	20.0	21.0	20.4	21.3	21.7
8H	20.2	21.1	20.6	21.4	21.8	20.1	21.0	20.6	21.4	21.8
12H	20.3	21.1	20.7	21.5	21.9	20.2	21.0	20.6	21.4	21.8
8H 4H	19.8	20.7	20.2	21.1	21.5	19.8	20.7	20.2	21.0	21.4
6H	20.5	21.2	20.9	21.6	22.0	20.4	21.1	20.9	21.5	22.0
8H	20.6	21.3	21.1	21.7	22.1	20.6	21.3	21.1	21.7	22.1
12H	20.7	21.3	21.2	21.7	22.2	20.7	21.3	21.2	21.7	22.2
12H 4H	19.8	20.6	20.3	21.0	21.4	19.8	20.6	20.2	21.0	21.4
6H	20.5	21.2	21.0	21.6	22.0	20.5	21.1	20.9	21.5	22.0
8H	20.7	21.3	21.2	21.7	22.2	20.7	21.2	21.2	21.7	22.2
Variations with the observer position at spacings:										
S = 1.0H	+ 0.2 / - 0.2					+ 0.2 / - 0.2				
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3				

CIE Pub.117, 1015 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 0.1)
 Area: 0.111111 m2

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-12-30

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:3.080m [K=1.0000]
 Remarks: PORTER

UTILIZATION FACTORS TABLE

Test:U:119.95V I:0.1300A P:11.294W PF:0.9497 Freq:59.98Hz Lamp Flux:1015.23x1 lm		
NAME: LED-6-S12W-5CCTWH-SQ	TYPE:	WEIGHT:
SPEC.:4000K 80	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	58	46	39	57	46	39	56	46	39	33
0.80	68	57	49	67	56	49	65	55	49	42
1.00	76	66	58	75	65	58	73	66	57	50
1.25	84	73	66	82	73	66	79	71	65	58
1.50	89	79	72	87	78	71	84	76	70	63
2.00	95	87	81	94	86	80	90	84	78	71
2.50	99	92	86	97	90	85	93	88	83	75
3.00	103	96	90	100	94	89	96	91	87	79
4.00	107	101	96	104	99	95	100	96	92	84
5.00	109	104	100	107	102	99	102	99	96	87
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended				SHRNOM = 1.25			

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-12-30

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:3.080m [K=1.0000]
 Remarks: PORTER

ISOCANDELA DIAGRAM

Test:U:119.95V I:0.1300A P:11.294W PF:0.9497 Freq:59.98Hz Lamp Flux:1015.23x1 lm		
NAME: LED-6-S12W-5CCTWH-SQ	TYPE:	WEIGHT:
SPEC.:4000K 80	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-12-30

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:3.080m [K=1.0000]
 Remarks: PORTER

AAI Figure

Test:U:119.95V I:0.1300A P:11.294W PF:0.9497 Freq:59.98Hz Lamp Flux:1015.23x1 lm		
NAME: LED-6-S12W-5CCTWH-SQ	TYPE:	WEIGHT:
SPEC.:4000K 80	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-12-30

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:3.080m [K=1.0000]
 Remarks: PORTER

ISOLUX DIAGRAM

Test:U:119.95V I:0.1300A P:11.294W PF:0.9497 Freq:59.98Hz Lamp Flux:1015.23x1 lm		
NAME: LED-6-S12W-5CCTWH-SQ	TYPE:	WEIGHT:
SPEC.:4000K 80	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-12-30

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:3.080m [K=1.0000]
 Remarks: PORTER

LED Avg.L Report

Test:U:119.95V I:0.1300A P:11.294W PF:0.9497 Freq:59.98Hz Lamp Flux:1015.23x1 lm		
NAME: LED-6-S12W-5CCTWH-SQ	TYPE:	WEIGHT:
SPEC.:4000K 80	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	2644
L_0~180 (75) av	2236
L_0~180 (85) av	1430
L_90~270 (65) av	2639
L_90~270 (75) av	2194
L_90~270 (85) av	877
L_45 (65) av	2663
L_45 (75) av	2237
L_45 (85) av	1228

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2021-12-30

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity:65.0%
 Test Distance:3.080m [K=1.0000]
 Remarks: PORTER

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators:
 Test Date: 2021-12-30

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.00.421
 Humidity: 65.0%
 Test Distance: 3.080m [K=1.0000]
 Remarks: PORTER

