



LUMINAIRE PHOTOMETRIC TEST REPORT

NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:Lotus LED Lights	SUR.:21cm*16cm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 98.43 lm/W
MODEL	6"	I _{max} (cd)	814.3	S/MH(C0/180)	1.21	
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.19	
RATED VOLTAGE(V)	120	TOTAL FLUX(lm)	1697.2	h UP, DN(C0-180)	0.0, 48.5	
NOMINAL FLUX(lm)	1697.2	CIE CLASS	DIRECT	h UP, DN(C180-360)	0.0, 51.5	
LAMPS INSIDE	1	h up(%)	0.0	CIBSE SHR NOM	1.25	
TEST VOLTAGE(V)	120	h down(%)	100.0	CIBSE SHR MAX	1.30	



C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2021-06-01

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:3.200m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

g	C0	C90	C180	C270					g	F zone	F total	%lum,lamp
10	790.9	796.6	801.7	795.6					0- 10	76.85	76.85	4.53,4.53
20	734.9	744.1	754.6	743.5					10- 20	218.3	295.2	17.4,17.4
30	631.6	639.1	662.9	646.2					20- 30	322.4	617.6	36.4,36.4
40	484.4	483.3	519.2	501.3					30- 40	358.6	976.2	57.5,57.5
50	318.8	309.7	351.3	335.7					40- 50	318.2	1294	76.3,76.3
60	165.5	152.4	192.3	180.2					50- 60	221.5	1516	89.3,89.3
70	68.38	65.17	77.09	74.57					60- 70	112.7	1629	96,96
80	28.65	27.63	36.85	33.77					70- 80	53.98	1683	99.1,99.1
90	0.4099	0.3181	1.606	0.2145					80- 90	14.61	1697	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1144.7 lm

%lum = 67.4%
 %lamp = 67.4%

Conical surface Flux(120deg): 1515.9 lm


%lum = 89.3%
 %lamp = 89.3%

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2021-06-01

g Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:3.200m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Lotus LED Lights	SUR.: 21cm*16cm	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	3749	2873
80	4914	4731
75	5684	5325
70	5955	5666
65	7374	6667
60	9857	9062
55	12400	11771
50	14774	14329
45	16931	16683

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2021-06-01

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.0.366
 Humidity: 65.0%
 Test Distance: 3.200m [K=1.0000]
 Remarks:

WEC AND CCEC

NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:Lotus LED Lights	SUR.:21cm*16cm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.258	.147	.046	.251	.143	.046	.238	.137	.044	.226	.130	.042	.215	.125	.040	
2.0	.248	.136	.042	.242	.133	.041	.231	.128	.040	.220	.124	.039	.211	.119	.038	
3.0	.234	.124	.037	.229	.122	.037	.219	.119	.036	.210	.115	.035	.201	.111	.034	
4.0	.219	.114	.034	.215	.112	.033	.206	.109	.033	.198	.106	.032	.190	.103	.032	
5.0	.206	.105	.030	.202	.104	.030	.194	.101	.030	.187	.099	.029	.180	.096	.029	
6.0	.193	.097	.028	.189	.096	.028	.183	.094	.027	.176	.092	.027	.170	.090	.027	
7.0	.182	.090	.025	.178	.089	.025	.172	.087	.025	.166	.085	.025	.161	.084	.025	
8.0	.171	.084	.023	.168	.083	.023	.163	.081	.023	.157	.080	.023	.153	.078	.023	
9.0	.161	.078	.022	.159	.077	.022	.154	.076	.022	.149	.075	.021	.145	.074	.021	
10.0	.153	.073	.020	.150	.073	.020	.146	.072	.020	.142	.070	.020	.138	.069	.020	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.177	.157	.138	.151	.134	.119	.103	.092	.082	.060	.054	.048	.019	.017	.015	
2.0	.166	.132	.103	.143	.114	.089	.098	.079	.062	.056	.046	.037	.018	.015	.012	
3.0	.158	.114	.079	.135	.098	.069	.093	.068	.048	.054	.040	.028	.017	.013	.009	
4.0	.150	.100	.063	.128	.087	.055	.088	.060	.038	.051	.035	.023	.016	.012	.007	
5.0	.142	.090	.051	.122	.078	.044	.084	.054	.031	.049	.032	.019	.016	.010	.006	
6.0	.135	.081	.042	.116	.070	.037	.080	.049	.026	.047	.029	.015	.015	.009	.005	
7.0	.129	.074	.036	.111	.064	.031	.077	.045	.022	.045	.027	.013	.014	.009	.004	
8.0	.123	.068	.031	.106	.059	.027	.073	.042	.019	.043	.024	.011	.014	.008	.004	
9.0	.117	.063	.027	.101	.055	.023	.070	.039	.017	.041	.023	.010	.013	.007	.003	
10.0	.112	.059	.024	.097	.051	.021	.067	.036	.015	.039	.021	.009	.013	.007	.003	

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2021-06-01

g Range: 0 - 90DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:3.200m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

NAME:		TYPE:					WEIGHT:				
SPEC.:		DIM.:					SERIAL No.:				
MFR.:Lotus LED Lights		SUR.:21cm*16cm					Shielding Angle:				
ceiling/cavity		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H	y = 2H	19.0	20.3	19.2	20.5	20.7	18.8	20.2	19.1	20.4	20.5
	3H	19.4	20.7	19.7	20.9	21.1	19.2	20.5	19.5	20.7	20.9
	4H	19.6	20.8	19.9	21.1	21.3	19.4	20.6	19.7	20.8	21.1
	6H	19.8	20.9	20.1	21.2	21.4	19.6	20.7	19.9	20.9	21.2
	8H	19.8	20.9	20.2	21.2	21.4	19.6	20.7	19.9	20.9	21.2
	12H	19.8	20.8	20.2	21.1	21.4	19.6	20.6	19.9	20.9	21.2
4H	2H	19.1	20.3	19.5	20.6	20.8	19.0	20.2	19.3	20.4	20.7
	3H	19.7	20.8	20.1	21.1	21.4	19.6	20.6	19.9	20.9	21.2
	4H	20.1	21.0	20.4	21.3	21.6	19.9	20.8	20.2	21.1	21.4
	6H	20.3	21.2	20.7	21.5	21.9	20.1	20.9	20.5	21.3	21.6
	8H	20.4	21.2	20.8	21.5	21.9	20.2	21.0	20.6	21.3	21.7
	12H	20.4	21.1	20.9	21.5	21.9	20.2	20.9	20.6	21.3	21.7
8H	4H	20.1	20.9	20.5	21.3	21.6	20.0	20.7	20.4	21.1	21.5
	6H	20.5	21.1	21.0	21.5	22.0	20.3	20.9	20.8	21.3	21.8
	8H	20.6	21.2	21.1	21.6	22.0	20.4	21.0	20.9	21.4	21.9
	12H	20.7	21.2	21.2	21.6	22.1	20.5	21.0	21.0	21.4	21.9
12H	4H	20.1	20.8	20.5	21.2	21.6	19.9	20.6	20.4	21.0	21.4
	6H	20.5	21.1	21.0	21.5	21.9	20.3	20.9	20.8	21.3	21.8
	8H	20.7	21.1	21.1	21.6	22.0	20.5	20.9	21.0	21.4	21.9
Variations with the observer position at spacings:											
S = 1.0H		+ 0.5 / - 0.6					+ 0.5 / - 0.7				
1.5H		+ 0.3 / - 0.3					+ 0.3 / - 0.3				
2.0H		+ 1.1 / - 1.3					+ 1.1 / - 1.3				

CIE Pub.117, 1697 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 1.8)

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2021-06-01

g Range: 0 - 90DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:3.200m [K=1.0000]
 Remarks:

UTILIZATION FACTORS TABLE

NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Lotus LED Lights	SUR.: 21cm*16cm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	65	54	48	64	54	48	63	54	48	42
0.80	75	65	58	74	64	58	72	64	58	52
1.00	83	74	67	82	73	67	80	74	67	60
1.25	90	81	75	88	80	74	86	79	74	67
1.50	94	86	80	92	85	80	90	83	78	72
2.00	100	93	88	98	92	87	95	90	85	78
2.50	103	97	92	101	95	91	97	93	89	81
3.00	106	100	96	104	99	94	100	96	92	85
4.00	109	104	100	107	102	99	103	99	96	88
5.00	111	107	103	108	105	102	104	101	99	90
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended				SHRNOM = 1.25			

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2021-06-01

g Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.0.366
 Humidity: 65.0%
 Test Distance: 3.200m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Lotus LED Lights	SUR.: 21cm*16cm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2021-06-01

Range: 0 - 90DEG
Interval: 1.0DEG
Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.0.366
Humidity: 65.0%
Test Distance: 3.200m [K=1.0000]
Remarks:

AAI Figure

NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:Lotus LED Lights	SUR.:21cm*16cm	Shielding Angle:

Flux out:1176 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2021-06-01

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:3.200m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2021-06-01

Page Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.0.366
 Humidity: 65.0%
 Test Distance: 3.200m [K=1.0000]
 Remarks:

