



LUMINAIRE PHOTOMETRIC TEST REPORT

NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Lotus LED Lights	SUR.: 21cm*16cm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 101.34 lm/W			
MODEL	6"	I _{max} (cd)	844.2	S/MH(C0/180)	1.21
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.19
RATED VOLTAGE(V)	120	TOTAL FLUX(lm)	1761.4	h UP, DN(C0-180)	0.0, 48.5
NOMINAL FLUX(lm)	1761.36	CIE CLASS	DIRECT	h UP, DN(C180-360)	0.0, 51.5
LAMPS INSIDE	1	h up(%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	120	h down(%)	100.0	CIBSE SHR MAX	1.30



C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2021-06-01

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.0.366
 Humidity: 65.0%
 Test Distance: 3.200m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

g	C0	C90	C180	C270					g	F zone	F total	%lum,lamp
10	820.2	826.0	831.2	825.0					0- 10	79.67	79.67	4.52,4.52
20	762.4	771.9	782.4	770.9					10- 20	226.4	306.1	17.4,17.4
30	655.6	662.9	687.5	670.1					20- 30	334.4	640.5	36.4,36.4
40	503.1	501.8	538.6	519.8					30- 40	372.1	1013	57.5,57.5
50	331.3	322.2	364.4	348.3					40- 50	330.3	1343	76.2,76.2
60	172.3	158.6	199.3	187.1					50- 60	230.1	1573	89.3,89.3
70	71.15	67.76	79.99	76.66					60- 70	117.0	1690	96,96
80	29.79	28.72	38.26	35.08					70- 80	56.07	1746	99.1,99.1
90	0.4267	0.3281	1.646	0.2208					80- 90	15.17	1761	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1187.5 lm

%lum = 67.4%

%lamp = 67.4%

Conical surface Flux(120deg): 1573.1 lm

%lum = 89.3%


%lamp = 89.3%

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2021-06-01

g Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:3.200m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Lotus LED Lights	SUR.: 21cm*16cm	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	3882	2982
80	5107	4921
75	5911	5546
70	6192	5895
65	7670	6945
60	10256	9442
55	12886	12254
50	15341	14914
45	17580	17341

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2021-06-01

G Range: 0 - 90DEG
 G Interval: 1.0DEG
 Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.0.366
 Humidity: 65.0%
 Test Distance: 3.200m [K=1.0000]
 Remarks:

WEC AND CCEC

NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:Lotus LED Lights	SUR.:21cm*16cm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.258	.147	.047	.251	.143	.046	.238	.137	.044	.226	.131	.042	.215	.125	.040	
2.0	.248	.136	.042	.242	.133	.041	.231	.128	.040	.220	.124	.039	.211	.119	.038	
3.0	.234	.125	.037	.229	.122	.037	.219	.119	.036	.210	.115	.035	.201	.111	.034	
4.0	.220	.114	.034	.215	.112	.033	.206	.109	.033	.198	.106	.032	.190	.103	.032	
5.0	.206	.105	.030	.202	.104	.030	.194	.101	.030	.187	.099	.029	.180	.096	.029	
6.0	.193	.097	.028	.190	.096	.028	.183	.094	.027	.176	.092	.027	.170	.090	.027	
7.0	.182	.090	.025	.178	.089	.025	.172	.087	.025	.166	.085	.025	.161	.084	.025	
8.0	.171	.084	.024	.168	.083	.023	.163	.081	.023	.157	.080	.023	.153	.078	.023	
9.0	.162	.078	.022	.159	.077	.022	.154	.076	.022	.149	.075	.021	.145	.074	.021	
10.0	.153	.073	.020	.150	.073	.020	.146	.072	.020	.142	.070	.020	.138	.069	.020	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.177	.157	.138	.151	.134	.119	.103	.092	.082	.060	.054	.048	.019	.017	.015	
2.0	.166	.132	.103	.143	.114	.089	.098	.079	.062	.056	.046	.037	.018	.015	.012	
3.0	.158	.114	.079	.135	.098	.069	.093	.068	.048	.054	.040	.028	.017	.013	.009	
4.0	.150	.100	.063	.128	.087	.054	.088	.060	.038	.051	.035	.023	.016	.012	.007	
5.0	.142	.090	.051	.122	.078	.044	.084	.054	.031	.049	.032	.019	.016	.010	.006	
6.0	.135	.081	.042	.116	.070	.037	.080	.049	.026	.047	.029	.015	.015	.009	.005	
7.0	.129	.074	.036	.111	.064	.031	.077	.045	.022	.045	.027	.013	.014	.009	.004	
8.0	.123	.068	.031	.106	.059	.027	.073	.042	.019	.043	.024	.011	.014	.008	.004	
9.0	.117	.063	.027	.101	.055	.023	.070	.039	.017	.041	.023	.010	.013	.007	.003	
10.0	.112	.059	.024	.097	.051	.021	.067	.036	.015	.039	.021	.009	.013	.007	.003	

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2021-06-01

g Range: 0 - 90DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:3.200m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

NAME:		TYPE:					WEIGHT:				
SPEC.:		DIM.:					SERIAL No.:				
MFR.: Lotus LED Lights		SUR.: 21cm*16cm					Shielding Angle:				
ceiling/cavity		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H	y = 2H	19.0	20.3	19.2	20.5	20.7	18.8	20.2	19.1	20.4	20.6
	3H	19.4	20.7	19.7	20.9	21.1	19.2	20.5	19.5	20.7	20.9
	4H	19.6	20.8	19.9	21.1	21.3	19.4	20.6	19.7	20.8	21.1
	6H	19.8	20.9	20.1	21.2	21.4	19.6	20.7	19.9	20.9	21.2
	8H	19.8	20.9	20.2	21.2	21.4	19.6	20.7	19.9	21.0	21.2
	12H	19.8	20.8	20.2	21.1	21.4	19.6	20.6	19.9	20.9	21.2
4H	2H	19.2	20.3	19.5	20.6	20.8	19.0	20.2	19.3	20.4	20.7
	3H	19.8	20.8	20.1	21.1	21.4	19.6	20.6	19.9	20.9	21.2
	4H	20.1	21.0	20.4	21.3	21.6	19.9	20.8	20.3	21.1	21.5
	6H	20.3	21.2	20.7	21.5	21.9	20.1	21.0	20.5	21.3	21.7
	8H	20.4	21.2	20.8	21.5	21.9	20.2	21.0	20.6	21.3	21.7
	12H	20.4	21.1	20.9	21.5	21.9	20.2	20.9	20.7	21.3	21.7
8H	4H	20.1	20.9	20.6	21.3	21.6	20.0	20.7	20.4	21.1	21.5
	6H	20.5	21.1	21.0	21.5	22.0	20.3	21.0	20.8	21.4	21.8
	8H	20.6	21.2	21.1	21.6	22.1	20.5	21.0	20.9	21.4	21.9
	12H	20.7	21.2	21.2	21.6	22.1	20.5	21.0	21.0	21.4	21.9
12H	4H	20.1	20.8	20.6	21.2	21.6	20.0	20.7	20.4	21.0	21.4
	6H	20.5	21.1	21.0	21.5	21.9	20.3	20.9	20.8	21.3	21.8
	8H	20.7	21.1	21.1	21.6	22.1	20.5	21.0	21.0	21.4	21.9
Variations with the observer position at spacings:											
S = 1.0H		+ 0.5 / - 0.6					+ 0.5 / - 0.7				
1.5H		+ 0.3 / - 0.4					+ 0.3 / - 0.3				
2.0H		+ 1.1 / - 1.3					+ 1.1 / - 1.3				

CIE Pub.117, 1761 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 2.0)

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2021-06-01

g Range: 0 - 90DEG
 g Interval: 1.0DEG
 Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.0.366
 Humidity: 65.0%
 Test Distance: 3.200m [K=1.0000]
 Remarks:

UTILIZATION FACTORS TABLE

NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Lotus LED Lights	SUR.: 21cm*16cm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	65	54	48	64	54	48	63	54	48	42
0.80	75	65	58	74	64	58	72	64	58	52
1.00	83	74	67	82	73	67	80	74	67	60
1.25	90	81	75	88	80	74	86	79	74	67
1.50	94	86	80	92	85	80	90	83	78	72
2.00	100	93	88	98	92	87	95	90	85	78
2.50	103	97	92	101	95	91	97	93	89	81
3.00	106	100	96	104	99	94	100	96	92	85
4.00	109	104	100	107	102	99	103	99	96	88
5.00	111	107	103	108	105	102	104	101	99	90
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended				SHRNOM = 1.25			

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2021-06-01

g Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.0.366
 Humidity: 65.0%
 Test Distance: 3.200m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Lotus LED Lights	SUR.: 21cm*16cm	Shielding Angle:




C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2021-06-01

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.0.366
 Humidity: 65.0%
 Test Distance: 3.200m [K=1.0000]
 Remarks:

AAI Figure

NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:Lotus LED Lights	SUR.:21cm*16cm	Shielding Angle:

Flux out:1220 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2021-06-01

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:3.200m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2021-06-01

Page Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.0.366
 Humidity: 65.0%
 Test Distance: 3.200m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:Lotus LED Lights	SUR.:21cm*16cm	Shielding Angle:

Table--1

UNIT: cd

C(DEG) \ g (DEG)	0	90	180	270																
0	844	844	844	844																
5	836	839	842	839																
10	820	826	831	825																
15	795	803	811	802																
20	762	772	782	771																
25	716	726	743	729																
30	656	663	687	670																
35	584	587	618	600																
40	503	502	539	520																
45	418	412	452	435																
50	331	322	364	348																
55	248	236	279	264																
60	172	159	199	187																
65	109	98.6	130	121																
70	71.2	67.8	80.0	76.7																
75	51.4	48.2	57.7	55.5																
80	29.8	28.7	38.3	35.1																
85	11.4	8.73	18.9	13.2																
90	0.43	0.33	1.65	0.22																

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2021-06-01

Range: 0 - 90DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-SPEX500_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:3.200m [K=1.0000]
 Remarks: