



LUMINAIRE PHOTOMETRIC TEST REPORT

NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Lotus LED Lights	SUR.: 21cm*16cm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 99.65 lm/W
MODEL	8"	I <sub>max</sub> (cd)	1005	S/MH(C0/180)	1.22	
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.22	
RATED VOLTAGE(V)	120	TOTAL FLUX(lm)	2139.7	h UP, DN(C0-180)	0.0, 49.2	
NOMINAL FLUX(lm)	2139.74	CIE CLASS	DIRECT	h UP, DN(C180-360)	0.0, 50.8	
LAMPS INSIDE	1	h up(%)	0.0	CIBSE SHR NOM	1.25	
TEST VOLTAGE(V)	120	h down(%)	100.0	CIBSE SHR MAX	1.30	



C Range: 0 - 360DEG  
 C Interval: 90.0DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: DAMIN  
 Test Date: 01 June 2021

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System: EVERFINE GO-SPEX500\_V1 SYSTEM V2.0.366  
 Humidity: 65.0%  
 Test Distance: 3.200m [K=1.0000]  
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

g	C0	C90	C180	C270					g	F zone	F total	%lum,lamp
10	980.6	982.2	987.8	986.6					0- 10	94.95	94.95	4.44,4.44
20	915.3	918.0	928.8	926.4					10- 20	270.2	365.2	17.1,17.1
30	804.2	809.6	825.9	821.4					20- 30	403.0	768.2	35.9,35.9
40	623.8	632.1	652.4	644.9					30- 40	457.2	1225	57.3,57.3
50	409.2	418.6	438.5	429.2					40- 50	410.0	1635	76.4,76.4
60	204.3	212.8	228.5	220.2					50- 60	283.1	1918	89.7,89.7
70	79.36	81.68	85.66	83.13					60- 70	135.9	2054	96,96
80	37.65	40.33	43.53	40.82					70- 80	64.80	2119	99,99
90	0.3888	0.3851	2.011	0.1959					80- 90	20.62	2140	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1442.2 lm

%lum = 67.4%

%lamp = 67.4%

Conical surface Flux(120deg): 1918.4 lm

%lum = 89.7%


%lamp = 89.7%

C Range: 0 - 360DEG  
 C Interval: 90.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:DAMIN  
 Test Date:01 June 2021

g Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.0.366  
 Humidity:65.0%  
 Test Distance:3.200m [K=1.0000]  
 Remarks:

**LUMINANCE LIMITATION CURVES**

<b>NAME:</b>	<b>TYPE:</b>	<b>WEIGHT:</b>
<b>SPEC.:</b>	<b>DIM.:</b>	<b>SERIAL No.:</b>
<b>MFR.: Lotus LED Lights</b>	<b>SUR.: 21cm*16cm</b>	<b>Shielding Angle:</b>



LUMINANCE cd/(m2)		
G( DEG)	C0/180	C90/270
85	5792	5909
80	6455	6911
75	6750	7002
70	6907	7106
65	8673	9065
60	12167	12661
55	15713	16185
50	18952	19379
45	21815	22190

C Range: 0 - 360DEG  
 C Interval: 90.0DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: DAMIN  
 Test Date: 01 June 2021

G Range: 0 - 90DEG  
 G Interval: 1.0DEG  
 Test System: EVERFINE GO-SPEX500\_V1 SYSTEM V2.0.366  
 Humidity: 65.0%  
 Test Distance: 3.200m [K=1.0000]  
 Remarks:

WEC AND CCEC

NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:Lotus LED Lights	SUR.:21cm*16cm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.258	.147	.047	.252	.143	.046	.238	.137	.044	.227	.131	.042	.216	.125	.040	
2.0	.248	.136	.042	.242	.133	.041	.231	.128	.040	.220	.124	.039	.211	.119	.038	
3.0	.234	.125	.037	.229	.122	.037	.219	.119	.036	.210	.115	.035	.201	.111	.034	
4.0	.220	.114	.034	.215	.113	.033	.206	.109	.033	.198	.106	.032	.191	.104	.032	
5.0	.206	.105	.030	.202	.104	.030	.194	.101	.030	.187	.099	.029	.180	.096	.029	
6.0	.193	.097	.028	.190	.096	.028	.183	.094	.027	.176	.092	.027	.170	.090	.027	
7.0	.182	.090	.025	.179	.089	.025	.172	.087	.025	.167	.085	.025	.161	.084	.025	
8.0	.171	.084	.024	.168	.083	.023	.163	.081	.023	.158	.080	.023	.153	.078	.023	
9.0	.162	.078	.022	.159	.078	.022	.154	.076	.022	.150	.075	.021	.145	.074	.021	
10.0	.153	.073	.020	.151	.073	.020	.146	.072	.020	.142	.071	.020	.138	.069	.020	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.177	.157	.138	.151	.134	.119	.103	.092	.082	.060	.054	.048	.019	.017	.015	
2.0	.166	.132	.103	.143	.114	.089	.098	.079	.062	.056	.046	.037	.018	.015	.012	
3.0	.158	.114	.079	.135	.098	.069	.093	.068	.048	.054	.040	.028	.017	.013	.009	
4.0	.150	.100	.063	.128	.087	.054	.088	.060	.038	.051	.035	.023	.016	.012	.007	
5.0	.142	.090	.051	.122	.078	.044	.084	.054	.031	.049	.032	.019	.016	.010	.006	
6.0	.135	.081	.042	.116	.070	.037	.080	.049	.026	.047	.029	.015	.015	.009	.005	
7.0	.129	.074	.036	.111	.064	.031	.077	.045	.022	.045	.027	.013	.014	.009	.004	
8.0	.123	.068	.031	.106	.059	.027	.073	.042	.019	.043	.025	.011	.014	.008	.004	
9.0	.117	.063	.027	.101	.055	.023	.070	.039	.016	.041	.023	.010	.013	.007	.003	
10.0	.112	.059	.024	.097	.051	.021	.067	.036	.015	.039	.021	.009	.013	.007	.003	

C Range: 0 - 360DEG  
 C Interval: 90.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:DAMIN  
 Test Date:01 June 2021

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.0.366  
 Humidity:65.0%  
 Test Distance:3.200m [K=1.0000]  
 Remarks:

UGR(Unified Glare Rating) Table

NAME:		TYPE:					WEIGHT:				
SPEC.:		DIM.:					SERIAL No.:				
MFR.:Lotus LED Lights		SUR.:21cm*16cm					Shielding Angle:				
ceiling/cavity		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H	y = 2H	19.1	20.5	19.4	20.6	20.8	19.2	20.6	19.5	20.8	20.9
	3H	19.4	20.7	19.7	20.9	21.1	19.6	20.8	19.8	21.0	21.3
	4H	19.6	20.8	19.9	21.0	21.3	19.7	20.9	20.0	21.2	21.4
	6H	19.8	20.9	20.1	21.1	21.4	19.9	21.0	20.2	21.3	21.6
	8H	19.8	20.9	20.2	21.2	21.5	20.0	21.0	20.3	21.3	21.6
	12H	19.9	20.9	20.2	21.2	21.5	20.0	21.0	20.4	21.3	21.6
4H	2H	19.3	20.5	19.6	20.7	20.9	19.4	20.5	19.7	20.8	21.0
	3H	19.8	20.8	20.1	21.1	21.4	19.9	20.9	20.2	21.2	21.5
	4H	20.0	21.0	20.4	21.3	21.6	20.1	21.1	20.5	21.4	21.7
	6H	20.3	21.1	20.7	21.5	21.8	20.4	21.3	20.8	21.6	22.0
	8H	20.4	21.2	20.8	21.5	21.9	20.6	21.3	21.0	21.7	22.1
	12H	20.5	21.2	20.9	21.6	22.0	20.6	21.3	21.1	21.7	22.1
8H	4H	20.1	20.9	20.5	21.2	21.6	20.2	21.0	20.6	21.3	21.7
	6H	20.5	21.1	21.0	21.5	22.0	20.6	21.3	21.1	21.7	22.1
	8H	20.7	21.2	21.1	21.7	22.1	20.8	21.4	21.3	21.8	22.2
	12H	20.8	21.3	21.3	21.7	22.2	21.0	21.4	21.4	21.9	22.4
12H	4H	20.1	20.8	20.5	21.2	21.6	20.2	20.9	20.6	21.3	21.7
	6H	20.5	21.1	21.0	21.5	22.0	20.7	21.2	21.1	21.6	22.1
	8H	20.7	21.2	21.2	21.7	22.1	20.9	21.4	21.4	21.8	22.3
Variations with the observer position at spacings:											
S = 1.0H		+ 0.5 / - 0.6					+ 0.5 / - 0.6				
1.5H		+ 0.3 / - 0.4					+ 0.3 / - 0.4				
2.0H		+ 1.1 / - 1.3					+ 1.1 / - 1.3				

CIE Pub.117, 2140 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 2.6)

C Range: 0 - 360DEG  
 C Interval: 90.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:DAMIN  
 Test Date:01 June 2021

g Range: 0 - 90DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.0.366  
 Humidity:65.0%  
 Test Distance:3.200m [K=1.0000]  
 Remarks:

UTILIZATION FACTORS TABLE

NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: Lotus LED Lights	SUR.: 21cm*16cm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	65	54	48	64	54	48	63	53	48	42
0.80	75	65	58	74	64	58	72	63	58	52
1.00	83	73	67	82	73	67	80	74	66	60
1.25	90	81	75	88	80	74	86	79	74	67
1.50	94	86	80	92	85	80	90	83	78	72
2.00	100	93	88	98	92	87	95	90	85	78
2.50	103	97	92	101	95	91	97	93	89	81
3.00	106	100	95	104	99	94	100	96	92	84
4.00	109	104	100	107	102	99	103	99	96	88
5.00	111	107	103	108	105	102	104	101	99	90
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended				SHRNOM = 1.25			

C Range: 0 - 360DEG  
 C Interval: 90.0DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: DAMIN  
 Test Date: 01 June 2021

g Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System: EVERFINE GO-SPEX500\_V1 SYSTEM V2.0.366  
 Humidity: 65.0%  
 Test Distance: 3.200m [K=1.0000]  
 Remarks:

**ISOCANDELA DIAGRAM**

<b>NAME:</b>	<b>TYPE:</b>	<b>WEIGHT:</b>
<b>SPEC.:</b>	<b>DIM.:</b>	<b>SERIAL No.:</b>
<b>MFR.: Lotus LED Lights</b>	<b>SUR.: 21cm*16cm</b>	<b>Shielding Angle:</b>




**C Range: 0 - 360DEG**  
**C Interval: 90.0DEG**  
**Test Speed: HIGH**  
**Temperature:25.3DEG**  
**Operators:DAMIN**  
**Test Date:01 June 2021**

**Range: 0 - 90DEG**  
**Interval: 1.0DEG**  
**Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.0.366**  
**Humidity:65.0%**  
**Test Distance:3.200m [K=1.0000]**  
**Remarks:**

**AAI Figure**

NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:Lotus LED Lights	SUR.:21cm*16cm	Shielding Angle:

Flux out:1523 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
 C Interval: 90.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:DAMIN  
 Test Date:01 June 2021

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.0.366  
 Humidity:65.0%  
 Test Distance:3.200m [K=1.0000]  
 Remarks:



Planar Illuminance Curve



C Range: 0 - 360DEG  
 C Interval: 90.0DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: DAMIN  
 Test Date: 01 June 2021

Page Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System: EVERFINE GO-SPEX500\_V1 SYSTEM V2.0.366  
 Humidity: 65.0%  
 Test Distance: 3.200m [K=1.0000]  
 Remarks:

