

ES-FSCOBC-24-Y-IP67

Round 8mm 3D Bendable LED Neonflex 24V 2.4W/ft IP67

Project: _____

Location: _____

Model # : _____ Qty: _____

Notes: _____

DESCRIPTION

Round 8mm LED Rope 3D Bendable Neonflex
 Seamless linear light - no diffused cover needed
 No aluminum channel needed
 No hotspots and with CRI 90+ for vibrant colors
 Reinforced design for stable performance when bending
 3 oz copper PCB and real gold wires for superb light maintenance
 Wires on both ends and 2 additional end caps included
 Available in 16ft length


INSTALLATION INSTRUCTIONS

1. Mount using the plastic brackets and screws included



2. You may cut it once and use the wires on both ends to power the pieces.
 Note that there are no cut marks printed.

Minimum Bending Diameter: 3 1/2" (90 mm)



SPECIFICATION (tolerance +/- 10%)	
Applications	Cove & Decorative Lighting
Power	2.4 W/ft (8 W/m)
Input	24V DC
Stock CCTs	2700 K 3000 K 4000 K 5000 K
Light output per meter	624 lm 640 lm 664 lm 690 lm
Efficiency	74 lm/W 76 lm/W 86 lm/W 86 lm/W
CRI	90 +
Available Length	16 ft (5 m)
Maximum Connection Length	16 ft (5 m)
Dimensions	5/16" round (8 mm)
Beam Angle	360°
Dimmable	Yes
LED Operation Type	Constant Voltage
IP Grade	IP 67
Approved Location	Wet Location
Operating Temperature	-4°F (-20°C) to +220°F (+105°C)
Cutttable Increment	1 5/16" (33 mm)
Minimum Bending Diameter	3 1/2" (90 mm)
Projected Life	70% Light Output at 50,000 Hours
Certification	c UL us
Warranty	5 Year Indoor / 3 Year Outdoor

ORDERING GUIDE

example: **ES-FSCOBC-24-Y-IP67-30K-16FT**

	- CCT (K)	- Length
ES-FSCOBC-24-Y-IP67	-27K	-16FT
	-30K	
	-40K	
	-50K	

Included in every package:

2 end caps, 16 transparent plastic mounting clips and 16 screws



Lotus LED Lights USA

250 H Street # 301, Blaine WA 98230 tel 360-200-5500
Hainesport NJ, Naples FL, Vancouver WA

www.LotusLEDLights.com

mailing addresses
warehouses

Lotus LED Lights CANADA

1080 Cliveden Ave # 6, Delta BC V3M 6J6 tel 604-538-3090
Delta BC & Mississauga ON